

ELO-BPC-17-6500

It adopts all-aluminum alloy structure, fanless and totally enclosed design, light and compact, with low power consumption. It is an industrial product specially designed for a variety of environments. It has rich interfaces, supports expansion, can meet the access of a variety of external devices, and supports 12V-36V wide voltage power supply; The complete machine has good scalability, practicability and EMC compatibility, and is widely used in industrial control, military industry, communication, power and network and other automation fields.

Features »

- Delicate and compact appearance, convenient installation
- Self-developed X86 architecture motherboard with multiple options
- Fanless totally enclosed design, low power consumption of the whole machine
- High integration, realizing WiFi/Bluetooth/Ethernet triple connection
- Abundant interfaces to meet the needs of various external equipment
- Industrial protection grade, stable system operation



















Product Model »

| Product model | Processor | | | | |
|---------------|-----------------------------|-----------------------------|-----------------------------|------------------------------|--|
| ELO-BPC-I7 | Intel Core I7-6500U, 2.5GHz | Intel Core I7-7500U, 2.7GHz | Intel Core I7-8565U, 1.8GHz | Intel Core I7-10510U, 1.8GHz | |










Product Installation >>



Product size







Product Specifications »

| ardware Configuration | | | | | | |
|-----------------------|---|-----------------------------|-----------------------------|-----------------------------|--|--|
| CPU | Intel Core I7-6500U, 2.5GHz | Intel Core I7-7500U, 2.7GHz | Intel Core I7-8565U, 1.8GHz | Intel Core I7-10510U, 1.8GH | | |
| Integrated Graphics | Intel HD Graphics 520 | Intel HD Graphics 620 | Intel Ultra HD Graphics 620 | Intel UHD 630 Graphics | | |
| Memory | 4G DDR4 (optional 8G/16G) | 4G DDR4 (optional 8/16/32G) | 4G DDR4 (optional 8/16/32G) | 8G DDR4 (optional 16/32/64 | | |
| Hard disk | 128G SSD (optional 256/512G) | | | | | |
| Audio chip | Onboard Realtek ALC662 HD audio decoding controller | | | | | |
| Chip card | Onboard 1 * Realtek RTL 811E Gigabit network card | | | | | |
| WIFI | Support 2.4G/5G dual-band WiFi | | | | | |
| Bluetooth | Bluetooth 4.0(optional) | | | | | |
| Resolution support | Above 800 * 600 | | | | | |
| System | Win10 Professional/Win10 Enterprise/Win10 Home/Win11 Professional Ubuntu 16.04.7/Ubuntu 18.04.6/Centos7.8/Centos7.9/Centos8.4 | | | | | |
| Power on | Support | | | | | |
| Remote Wakeup | Support | | | | | |
| Automatic reset | Support | | | | | |
| HD support | 1080P | | | | | |
| eliability parameters | | | | | | |
| Working temperature | -20 °C ~65°C | | | | | |
| Storage temperature | -40 °C ~80 °C | | | | | |
| Operating humidity | Humidity: 95% non condensing | | | | | |
| Vibration protection | IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis | | | | | |
| Impact protection | IEC 60068-2-27, half sine wave, duration 11ms | | | | | |
| Product certification | CCC/CE/FCC/EMC/CB/ROHS | | | | | |
| ther parameters | | | | | | |
| Power input | 12V-36V power input | | | | | |
| Static power | 15W | | | | | |
| Chassis structure | The aluminum alloy on the case surface has good seismic resistance and impact resistance | | | | | |
| Body color | Gun black | | | | | |
| Overall size | 199.5 * 213.1 * 58.3mm (length * width * height) | | | | | |
| Operating Weight | 1.9KG | | | | | |
| Installation method | Support desktop and rack installation | | | | | |
| Warranty policy | Three years (one year free warranty) | | | | | |

Product Installation »

